DLS SERIES Residential Lighting



DLS6-MCT-PIR



Disk lights have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications.

eatures

- Die-cast Aluminum. Powder-Coated
- Unique DOB (Driver On Board) LED Board Enclosed in Clear PC Cover for Better Wet Location Performance

Technical Specifications

Electrical:

- Voltage: 120V AC
- Power Factor: >0.90
- Wattage: 15W
- Efficacy: 67 LPW

Mechanical:

- White Finish
- Die-cast Aluminum. Powder-Coated
- Gasket: Closed Cell Neoprene Foam Gasket
- Fits on 4"Octagonal (4O) or 3"Octagonal (3O) Electrical **Boxes**
- Recessed Mounting Kit Included for Recessed/Retrofit Installation
- Maximum Ambient Temperature: 104°F
- Rated life: 50,000 hrs
- Sensor Hold Time: 30s
- Sensor Mounting Height: 16.4FT maximum
- Sensor Detection Angle: 120°

Other Models:

• 9W | 540LM | DLS4-MCT-PIR

• 20W | 1200LM | DLS8-MCT-PIR

• 25W | 1500LM | DLS10-MCT-PIR • 30W | 1800LM | DLS12-MCT-PIR





Color Rendering Index: CRI ≥ 90

Applications:

Disk lights have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

- Integrated PIR (Passive Infra Red) Motion Sensor
- **Closed Cell Neoprene Foam Gasket**
- Multi CCT (Selectable Switch on LED Board Under the Lens)


Lighting:

- Lens: White Translucent Acrylic
- LED: Unique DOB (Driver On Board) LED Board Enclosed in Clear PC Cover for Better Wet Location Performance
- Dimming: TRIAC Dimming (Using Standard TRIAC
- LED Dimmers)
- Total Lumens: 1000LM
- Color Temperatures: 3000K/ 4000K/ 5000K
- Multi CCT (Selectable Switch on LED Board Under the Lens)
- 5-Year Warranty





Customer Name: Project Name: Note: Type: 5 4/5' 5 4/5" x 1 1/4"



WESTGATE

