


DIMENSIONS:

47.8"(L) x 23.82"(H) x 1.69"(D)



- LPNG-2X4-7KLM-50K-D
- LPNG-2X4-7KLM-40K-D
- LPNG-2X4-7KLM-35K-D
- LPNG-2X4-7KLM-27K-D

LED BLACKLIT PANEL LIGHT, 100~277 VAC

Ideal for hotel, offices, retail outlets, restaurant, parking garages, storage room, conference room, education facilities and more.

ELECTRICAL SPECIFICATIONS:

- Voltage: 100-277VAC, 50/60Hz
- Wattage: 60W
- Current: 1850mA
- Power factor: >0.90
- Efficacy: 108~132LM/W
- THD: <20%

HOUSING SPECIFICATIONS:

- External driver mounted on top
- PMMA Light Guided Panel (LGP) does not turn yellow.
- Earthquake hooks and suspension hooks pre-installed
- Operating temperature: -68°F ~ 104°F
- Lifespan: 50,000 Hrs.

MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
LPNG-2X4-7KLM-50K-D	60W	100~277VAC	7920LM	5000K
LPNG-2X4-7KLM-40K-D	60W	100~277VAC	7920LM	4000K
LPNG-2X4-7KLM-35K-D	60W	100~277VAC	7560LM	3500K
LPNG-2X4-7KLM-27K-D	60W	100~277VAC	6480LM	2700K

LIGHTING SPECIFICATIONS:

- Dimming: 0~10V dimmable
- LED Type: 2835SMD
- Total lumens: 7920LM/7560LM/6480LM
- Color temperature: 5000K/4000K/3500K/2700K
- Color rendering index: >80
- Soft and wide light emitting
- No infrared rays, no ultraviolet radiation, no thermal effect
- No flickering, no humming, no RF interference

WARRANTY: 5 years

CERTIFICATIONS:UL,DLC

